Cheer your world with innovation www.ledcheer.com

# Commercial LED Display AO Series

All-In-One LED Display

All in one LED display screen integrates all the necessary components into a single unit, providing a seamless and compact solution for displaying content.













Low Failure Rate


## Parameter >>

Model	CHEER-AO1.25 108"	CHEER-AO1.56 135"	CHEER-AO1.875 163"	CHEER-AO2.3 216"
Pitch	P1.25	P1.56	P1.875	P2.3
Product size	2400×1350×51mm	3000×1687.5×51mm	3600×2025×51mm	4800×2700×51mm
Resolution	1920×1080Pixles	1920×1080Pixles	1920×1080Pixles	1920×1080Pixles
Cabinet Weight	105/kg	145/kg	190/kg	240/kg
Gray Scale	16bit			
Refresh Rate	3840Hz			
Brightness Intensity	600–1000cd/m്((8 levels adjustable)			
Viewing Angle	160°/160°			
Average Power	900W/Pcs	900W/Pcs	1000W/Pcs	2720W/Pcs
Installation	Wall hanging/floor/hoisting			
Lifetime	100,000Hours			
Operator Voltage	AC100-220V/50/60HZ			
Working Temperature	-20°C~60°C			
Working Humidity	10-90%RH			

# GOB/COB



## **Highly Integrated**



### **Shutter style 3D - immersive experience**



### Dual operating system

Supports seamless switching betweer Windows and Android dual systems, and supports customized apps







applications





Supports multiple expansion modes

Customizable non-standard sizes to meet various scenario applications

Wide **Application** 



**1** 4 23 / PAGE 24/PAGE ▶▶